SWITCHES

4

CM-60

6" ROUND ALL-ACTIVE SWITHCES





CM-60/2

FEATURES

- LARGE, EASY TO OPERATE SWITCHES
- 6" ROUND
- ALL-ACTIVE DESIGN REQUIRES MINIMAL ACTUATION FORCE
- DURABLE STAINLESS STEEL OR SOLID BRASS CONSTRUCTION
- MEETS ADA REQUIREMENTS
- FLUSH MOUNT OR SURFACE MOUNT
- UL/CSA APPROVED SPDT MOMENTARY SWITCH, RATED 15 AMPS @ 30V DC
- VARIOUS LOGOS & MESSAGES
- ARCHITECTURAL FINISHES



CM-60/3

DESCRIPTION

Camden Door Controls CM-60 Series all-active switches are heavy-duty, ADA-compliant door controls. The 6" round faceplates are stainless steel or solid brass, and the assembly is designed for easy installation in single-gang electrical boxes, or, with included adapter plate – double-gang and 4x4 boxes. The SPDT and optional DPDT switches are UL/CSA approved, and rated 15 amps @ 30 VDC.



CM-60/4

APPLICATION

Camden all-active switches are designed for areas where an easy-to-activate, high-visibility switch is desired. Ideal for high-traffic areas, hospitals, wheelchair access, seniors' residences, etc. They can be surface or flush mounted.

Camden all-active switches are designed to control electric strikes, electromagnetic locks and automatic doors. They may also be used for shunting, bypassing alarms, request to exit, timed functions and many other applications.

The switches are made for high frequency usage, for both indoor and outdoor environments. Camden switches are versatile, and can be supplied in various configurations and finishes, to suit any commercial, industrial or residential application.

ARCHITECTS / ENGINEERS SPECIFICATIONS

The switches to be used throughout the complex shall be Camden Door Controls CM-60 all-active switches.

The switches shall be easy-to-activate, ADA compliant and 6" round in diameter. Switches shall be all-active, whereby pressing any part of the faceplate will activate the device. Faceplates shall be constructed of 18-gauge stainless steel or solid brass, and have concealed mounting screws for tamper resistance. Switches shall use plastic spacers and rubber dampers for noise reduction. Switches shall be rated at a minimum of 15 amps @ 30 VDC.

Their design shall allow mounting in single-gang electrical boxes, or, with included adapter plate – double-gang and 4x4 boxes.

ORDERING INFORMATION

All CM-60 series all-active switches are complete ready-to-install assemblies. They are supplied with stainless steel Allen screws and Allen wrench for mounting.

MODEL	DESCRIPTION
CM-60/1	NO EMBOSSING
CM-60/2	EMBOSSED WITH WHEELCHAIR LOGO IN BLUE
CM-60/2AL	EMBOSSED WITH WHEELCHAIR LOGO IN BLUE AND LEFT ARROW
CM-60/2AR	EMBOSSED WITH WHEELCHAIR LOGO IN BLUE AND RIGHT ARROW
CM-60/3	EMBOSSED WITH 'PUSH TO OPEN' LOGO IN BLACK
CM-60/3F	EMBOSSED WITH 'POUSSEZ POUR OUVRIR' LOGO IN BLACK
CM-60/4	EMBOSSED WITH WHEELCHAIR LOGO AND 'PUSH TO OPEN' LOGOS IN BLUE
CM-60/4AL	EMBOSSED WITH WHEELCHAIR LOGO AND 'PUSH TO OPEN' LOGOS IN BLUE WITH LEFT ARROW
CM-60/4AR	EMBOSSED WITH WHEELCHAIR LOGO AND 'PUSH TO OPEN' LOGOS IN BLUE RIGHT ARROW
CM-60/4F	EMBOSSED WITH WHEELCHAIR LOGO AND 'POUSSEZ POUR OUVRIR' LOGOS IN BLUE
CM-60/8	EMBOSSED WITH 'PUSH TO LOCK' LOGO
CM-60/8D	EMBOSSED WITH 'PUSH TO LOCK' DOOR LOGO
CM-60/8F	EMBOSSED WITH 'POUSSEZ POUR VERROUILLER' LOGO

OPTIONS/FINISHES:

OFTIONS/FINISHES:		
- DP	ADD DP TO PRODUCT # TO ORDER DPDT SWITCH INSTEAD OF SPST SWITCH (USE SPECIAL MOUNTING PLATE/TEMPLATE)	
- WR	ADD WR TO PRODUCT # FOR WEATHER RESISTANT BOOT	
- WT	ADD WT TO PRODUCT # FOR BOOT AND WATER TIGHT COATING	
- AL	ADD AL TO PRODUCT # FOR ARROW LEFT	
- AR	ADD AR TO PRODUCT # FOR ARROW RIGHT	
- AB	ADD AB TO PRODUCT # FOR ANTIQUE BRASS FINISH (US5/C5)	
- PB	ADD PB TO PRODUCT # FOR POLISHED BRASS FINISH (US3/C3)	
- SB	ADD SB TO PRODUCT # FOR SATIN BRASS FINISH (US4/C4)	
- OB	ADD OB TO PRODUCT # FOR OIL RUB BRONZE FINISH (US10B/C10B)	







