



## AL – Series



### **Dependable performance for high traffic commercial applications.**

At Schlage we know that every product you specify has to stand up to constant use, while meeting your needs for security at every level. Our AL-Series locks are designed to deliver ADA compliant accessibility and constant, reliable performance. The AL-Series is best for buildings with medium to high traffic flow, such as interior office doors, banks, retail spaces and hotel guest areas. With a Grade 2 ANSI rating, and styles and finishes to suit your building's design, the AL-Series fits right where you need it.

### **The lever that looks as good as it performs.**

- Cold-rolled steel, machined and threaded hubs, and locking nuts prevent loosening of the lockset by securely bolting chassis to the door
- Large diameter of mounting plate and rose covers new ANSI hollow metal door cutout
- Patented door range adjuster allows quick and easy adjustment for doors ranging from 1 3/8" to 1 7/8" (35 mm to 48 mm) thick

### **Door Handing**

All Schlage locks are reversible. Hand information is necessary to ensure proper cylinder orientation in keyed functions, and finish of latchbolt and strike for locks that are to be installed on reverse bevel doors.

### **Specifications**

**Handing:** Non-handed.

**Door Thickness:** 1 3/8" to 1 7/8" (35 mm to 48 mm) standard. 2" (51 mm) optional.

**Backset:** 2 3/4" (70 mm) standard. 2 3/8" (60 mm), 3 3/4" (95 mm) and 5" (127 mm) optional.

**Front:** Steel. 2 1/4" x 1 1/8" square corner, beveled, for 2 3/4" backset standard. Optional 1" square corner, 1" radius corner, and non-UL drive-in / round face. For availability with specific backsets.

**Lock Chassis:** Steel, zinc dichromated for corrosion resistance

**Latch Bolt:** Brass, chrome plated, 1/2" throw, deadlocking on keyed and exterior functions.

**Exposed Trim:** Wrought brass and bronze. Levers are pressure cast zinc, plated to match finish symbols.

**Strike:** ANSI curved lip strike 4 7/8" x 1 1/4" x 1 1/4" lip to center standard. Optional strikes, lip lengths and ANSI wrought strike box available.

**Cylinder & Keys:** 6-pin patented Everest 29 S123 keyway standard with two nickel silver keys per lock.

**Keying Options:** Interchangeable core and Primus® high security cylinders. Master keying, grand master keying, and construction keying.

**Warranty:** Three-year limited.